

CyBox AP 2-W

RAILWAY ACCESS POINT WITH WI-FI 5 DUAL RADIO

WESTERMO

DESCRIPTION

SYSTEM ARCHITECTURE	Dual-Core CPU T1023, 1200 MHz 1 GB RAM, 128 MB Flash
POWER SUPPLY	24 to 110 VDC, wide-range power supply (compliant to EN 50155)
AMBIENT TEMPERATURE	depending on temperature class of Wi-Fi module Class OT4, -40.. +70 °C (85 °C) operating or Class OT3, -25.. +70 °C (85 °C) operating -40.. +85 °C storage
STANDARDS	EN 50155

STANDARD CONFIGURATIONS

ORDER NO.	LAN 1 (M12 X- CODED)	LAN 2 (M12 X- CODED)	ETHERNET SWITCH	WI-FI 1 802.11AC 3X3 MIMO	WI-FI 2 802.11AC 3X3 MIMO	INPUT PSU 24 - 110 VDC (M12 A-CODED)	INPUT POE+ ON LAN 1	USB 2.0/RS232 (M12 8-PIN A-CODED)	BYPASS RELAYS	ANTENNA CONNECTORS	ANTENNA COMBINERS	IP CLASS
CYAPW-1050V0	1 Gbit	1 Gbit	-	●	●	●	●	●	-	6x QLS	-	IP40
CYAPW-1053V0	1 Gbit	1 Gbit	-	●	●	●	-	●	●	6x QLS	-	IP40
CYAPW-1061V0	1 Gbit	1 Gbit	●	●	●	●	●	●	-	6x QLS	-	IP40
CYAPW-1062V0	1 Gbit	1 Gbit	●	●	●	●	-	●	●	6x QLS	-	IP40
CYAPW-1200V0	1 Gbit	1 Gbit	-	●	●	●	●	●	-	3x QLS	●	IP40

Further information on www.eltec.com and www.westermo.com

Westermo Eltec GmbH
Galileo-Galilei-Str. 11
55129 Mainz
Germany

Phone +49 6131 918 100
Email info.eltec@westermo.com
www eltec.com | westermo.com

Copyright © 2021 by Westermo Eltec GmbH, Mainz.
All trademarks are the property of their owners. All rights reserved.

Revision: **2.0** | Date: **16.02.2024**