

CyBox AP 3-W

RAILWAY ACCESS POINT WITH WI-FI 5 WAVE 2 DUAL RADIO

WESTERMO

DESCRIPTION

SYSTEM ARCHITECTURE	Dual-Core CPU T1023, 1200 MHz 1 GB RAM, 128 MB Flash
POWER SUPPLY	24 to 110 VDC, wide-range power supply (compliant to EN 50155)
AMBIENT TEMPERATURE	depending on temperature class of Wi-Fi module Class OT4, -40.. +70 °C (85 °C) operating or Class OT3, -25.. +70 °C (85 °C) operating -40.. +85 °C storage
STANDARDS	EN 50155

STANDARD CONFIGURATIONS

ORDER NO.	LAN 1 (M12 X-CODED)	LAN 2 (M12 X-CODED)	WI-FI 1 802.11AC WAVE 2 4X4 MU-MIMO	WI-FI 2 802.11AC WAVE 2 4X4 MU-MIMO	INPUT PSU 24 - 110 VDC (M12 A-CODED)	INPUT POE+ ON LAN 1	USB 2.0/RS232 (M12 8-PIN A-CODED)	ANTENNA CONNECTORS	ANTENNA COMBINERS	IP CLASS
CYAPW-3010V0	1 Gbit	1 Gbit	●	●	●	●	●	4x QLS	●	IP40
CYAPW-3030V0	1 Gbit	1 Gbit	●	●	●	●	●	8x QLS	-	IP40

Further information on www.eltec.com and www.westermo.com